

Crushproof ACT Hose

Date 7/04

Part No. ACTXXX

Type 1 Hose - Crushproof ACT Hose

TAB 1-A2

The Crushproof convoluted design has been specifically formulated to handle 600°F temperatures. The hose, which does **not** contain a wire helix, returns back to its' original shape if "crushed" by any vehicles or other machinery. This hose is ideal for application where the hose may be left on the floor or used in underground applications.

The Crushproof **ACT** Hose is available in 4" 5" and 6" diameter is designed to be used with larger cars & trucks. It is also available with a wire helix to prevent kinking. If the hose is going to be used in an application where it may be left on the floor and run over, then you would need a hose without the wire helix. If the hose will be installed on a hose reel, the hose will flatten out so the wire helix would be required. If a hose with the wire helix is run over, it will be ruined.

This product should always be used with the proper tailpipe adapter for your application.



Crushproof ACT Hose shown above without wire reinforcement.

Crushproof ACT Hose (without wire) Options:

Part No	Description
ACT400	Crushproof 4" x 11' ACT Rubber Hose without wire reinforcement
ACT500	Crushproof 5" x 11' ACT Rubber Hose without wire reinforcement
ACT600	Crushproof 6" x 11' ACT Rubber Hose without wire reinforcement