## **CRUSHPROOF GARAGE EXHAUST HOSE**



| Adapters Sizes/ Styles  | 2" (50mm)<br>Motorcycle | 2.5" (63mm)<br>Compact Car | 3" (76mm)<br>Average Car | 3.5" (89mm)<br>Average Car | 4" (102mm)<br>Light Truck | 5" (125mm)<br>Diesel Truck | 6" (150mm)<br>Diesel Truck |
|---|-------------------------|----------------------------|--------------------------|----------------------------|---------------------------|----------------------------|----------------------------|
| Flarelock Hose Flared ends allow multiple pieces to connect.            | FLT200                  | FLT250                     | FLT300                   | FLT350                     | FLT400                    |                            |                            |
| ACT Hose  Designed for diesel & gas trucks. Ideal for overhead systems. |                         |                            |                          |                            | ACT400<br>ACT 40-20       | ACT500                     | АСТ600                     |
| ACT w/ Wire  A wire inside of the hose to Prevent kinking.              |                         |                            |                          |                            | ACT400W/<br>11            | ACT500W/<br>11             | ACT600W/<br>11             |
| Dyno Hose Special rubber blend for use w/ dynamometers.                 |                         |                            |                          |                            | ACT400<br>DYNO            |                            |                            |
| Hose Reel Hose Designed for hose reels and overhead systems.            |                         |                            |                          |                            | CPRH 400                  | CPRH 500                   | CPRH 600                   |